

### **HYDRAULIC BROOMER (ROAD SWEEPER)**



Nylon Bristles ensure proper cleaning on WMM, Asphalted surface and WBM - Metaling surface.

The angular screw type brush section sweeping and pushing dust to left hand side of road.

3 nos. height adjusting screws with operating handles are provided for perfect and firm contact of brush roller with ground during sweeping plain or slopped ground surfaces of road. Roller is lifted using these 3 screws, while in transporting the machine. Screw type handle to adjust the brush section to earthing the road surface for sweeping. Total three such handles for adjustment up - down height for traveling and sweeping.





#### **TECHNICAL SPECIFICATION**

MODE OF OPERATION	Hydraulic Broom by tractor hyd. system.		
SWEEPING WIDTH	2.25 meter clear sweeping in hyd. Broom.		
DUST COLLECTION	Left hand side.		
SWEEPING ADJUSTMENTS	Adjustable on both sides as per the Slope of Road.		
WHEEL	Two Heavy Duty Wheels.		
MATERIAL OF BRUSH	Harden Nylon Bristles.		
SUITABLE TO USE FOR	Metaling Surface (WBM). Wet Mix Macadam Surface. Asphalt Road Surface.		

SWEEPING SPEED	7 to 15 Km/hr.	DIAMETER OF BRUSH	450 mm
RUNNING SPEED	25 Km / hr.	WHEELS FOR DRIVE	2 Nos. Tyre



# **HYDRAULIC BROOMER (ROAD SWEEPER WITH BUCKET)**



#### **TECHNICAL SPECIFICATION**

Mode of Operation	Hydraulic Broom by tractor hyd. system.	
Sweeping width	2 meter clear sweeping	
Dust collection	In Bucket	
Material of Brush	Harden Nylon Bristles.	
Suitable to use for	Wet Mix Macadam Surface. & Asphalt Road Surface.	

Sweeping Speed	7 to 15 Km/hr.	Diameter of Brush	450 mm
Running Speed	25 Km/hr.	Wheels for Drive	2 Nos. Solid Rubber Tyre

(Note: Specifications / Descriptions / Dimensions are indicative and subject to change without notice due to modification alteration or custom engineering)







## **HYDRAULIC BROOMER** (ROAD SWEEPER WITH BUCKET & SIDE BRUSH)



#### **TECHNICAL SPECIFICATION**

Mode of Operation	Hydraulic Broom by tractor hyd. system.	
Sweeping width	2 meter clear sweeping	
Dust collection	In Bucket	
Material of Brush	Harden Nylon Bristles.	
Suitable to use for	Asphalt Road Surface.	
Right Side Brush Drive	Hyd. Motor	
Right Side Brush Uses	Divider angle dust swiped in to bucket	

Sweeping Speed	7 to 15 Km/hr.	Diameter of Brush	450 mm
Running Speed	25 Km/hr.	Wheels for Drive	2 Nos. Solid Rubber Tyre

(Note: Specifications / Descriptions / Dimensions are indicative and subject to change without notice due to modification alteration or custom engineering)



